

h/p/cosmos walking

h/p/cosmos mercury 4.0



[Illustration non-binding]

sports

pos.	order number	product description	price
01	cos0C197080000	Running machine h/p/cosmos mercury 4.0 Running surface 150 x 50 cm, Speed 0 ... 22 km/h, Elevation 0 ... 24 %, Drive motor 2.2 kW, integrated UKK 2 km walk test with evaluation of the fitness-index, Interface port COM1 for PC or printer, incl. software h/p/cosmos para control for remote control and supervision	
02	cos00097010035	Interface connection cable RS232, 10 m	
03	cos11020	Bottle holder for handrail	
04	cos14954	h/p/cosmos satellite print - printer-Set for direct documentation without PC, incl. laser printer, RS232 converter with cable, printer trolley	
05	cos00097010017	Transport in cardboard box (assembled or part-assembled), installation & instruction included	

System h/p/cosmos walking

E & OE. Subject to alterations without prior notice. System- and Software-training as well as workshops on request. Special accessories and custom made running machines for special applications on request. Manufacturer: h/p/cosmos sports & medical gmbh, Am Sportplatz 8, DE 83365 Nussdorf-Traunstein / Germany, phone + 49 / 8669 / 86 42 0, fax + 49 / 8669 / 86 42 49
sales@h-p-cosmos.com www.h-p-cosmos.com

running machine:	h/p/cosmos mercury 4.0 treadmill ergometer) with user terminal (display & keyboard) stand-alone & remote control via RS232.
applications:	running for sports & fitness, not for medical use
running surface:	length 150 cm / 59.05", width 50 cm / 19.68", access height 18 cm - special size on request - shock load reduction for the joints - belt surface with non slippery material - max. permissible load: 200kg (440 lbs)
speed range:	0 ... 22.0 km/h / 0...6.1 m/sec. / 0...13.6 mph) special speed up to 30 km/h on request
acceleration:	7 levels (in 3...131 sec. from 0 to max. speed) also for deceleration
elevation:	0 ... 24 % (0 ...1 3.5°) adjustable electr., resolution 0.1% (-24%...+24% when using the reverse belt rotation) special elevation on request, electronic motor break system prevents from accelerating when running at max. elevation
running direction:	switch for reversing running belt direction, (option extra charge) safety-harness required for reverse
motor system:	2.2 kW (3.0 HP) 3phase A.C. motor (maintenance free)
power transmission:	Poly-V-Belt drive (very quiet operation)
safety systems:	CE, IEC EN 60335-1 (VDE 0700); IEC EN 60601-1-2 (EMC approval); IEC EN 60601-1-4 VDE 0701; EN 957-1; EN 957-2; EN 957-6; emergency-stop-switch
display (resolutions):	6 LCD displays, 4 LED for operation mode, 20 LEDs: display of units, profile no, steps, etc. speed (0.1 km/h or m/sec or m/min or mph), time (00:00) in hours, minutes & seconds, elevation (0.1 %/ °) distance (1 meter ... 999.9 km or miles), METS (1 MET) program step/number,energy (1kJ/ kcal), fitness index (1) power (1 Watt), heart rate (1 bpm/beat per minute)
heartrate monitoring:	POLAR wireless, 1-channel receiver, ECG-accurate, measuring and display beat to beat
heartrate control:	automatic control of speed and elevation according to programmed target heart rate („cardio mode“)
interface digital:	1x RS232 COM1 incl. PC-, CosCom-, Blood-Pressure-Monitor-, ECG-, Ergospirometry- & series printer protocol (optional 2nd RS232 interface COM2: extra charge)
programs:	20 programs / profiles - 6 exercise profiles (scalable, 131 variations) - 10 test profiles (UKK Walktest, Cooper, Conconi, Graded Test etc.) - 4 free defineable profiles, 10 steps each
free PC software:	h/p/cosmos para control for display & remote control.
software:	h/p/cosmos para graphics & para analysis. (option extra charge) PC software for monitoring, recording & control
colour of frame:	grey aluminium RAL 9007 (powder coated), other colours available on request
handrails:	steel tube handrails on both sides, open shape to the front, frontbar handle available
voltage supply:	220/240 Volt, 50/60 cycles (Hz), 1 phase AC, 15 Amps special voltage supply available on request
size of frame:	length 210 cm / 82.67", width 82 cm / 32.28", height 136 cm / 53.53"
weight:	approx. 190 kg / 420 lbs

E & OE. Subject to alterations without prior notice. Further details & accessories on request.

Authorised h/p/cosmos dealer